



Notes

1. All dimensions in millimetres.
2. Tactile paving to be buff in colour.
3. The orientation of raised texture MUST align with the direction of travel on the crossing.
4. Tactile paving colour varies with crossing type. At controlled crossings use red paving. At uncontrolled crossings use buff paving.
5. Controlled crossings are Pelican, Toucan, Puffin, Zebra, Pegasus and signalised junctions which incorporate illuminated and audible warning pedestrian control.
6. Uncontrolled crossings are any crossing not mentioned in Note 5.
7. All requirements to comply with principles set out in DETR 'Guidance on the use of Tactile Paving surfaces' 1998.
8. Tactile paving shall be concrete 'Dimple' blocks (unless otherwise stated) 200mm x 133mm x 60mm laid on 30mm sand, 100mm AC20 dense binder and 150mm type 1 sub-base.
9. Area of tactile block must be surrounded by 150mm x 50mm footway edgings (See SD/11/4)
10. Minimum size of cut block shall be one third.
11. 400mm x 400mm x 50mm 'Dimple' slabs may be used to maintain existing areas where less than 20% require replacement.
12. Type 3 'flush' kerbs to be bull nose finish with a nominal upstand of 6mm.

Rev:	Date:	Description:	Approved by:
AMENDMENT DETAILS			



Checked by:	GP	Approved by:	SB
-------------	----	--------------	----

ISSUED	12/05/17
--------	----------

Layout of Blister Surfacing at Indented Uncontrolled Crossing at Acute Angled Junction

SD/11/11 <small>Standard Detail Number</small>	<small>Revision Number</small>
--	--------------------------------

This is a typical detail and may require conversion to a full scheme specific drawing.

NOT TO SCALE
(all units in millimetres)

Disclaimer : Before making use of this detail, any designer or third party must ensure that it satisfies all requirements of the scheme to which it is being applied. Lincolnshire County Council accept no responsibility for third party use of this Standard Detail.