






Notes

1. Post face to kerb face;  
Straight post = 0.7m min.;  
Cranked and stub posts = 0.5m min.
2. Crossing widths;  
2.4m absolute min for exact dimensions see design drawing.
3. Kerb upstand at crossing to be 6mm ±3mm tolerance. To be agreed with Traffic Signals. See SD/11/31.
4. Maximum gradient of ramp 8% although preferable 5%
5. Crossing studs to be 100mm Ø circular cored thermoplastic at 500mm centres.
6. The orientation of raised texture **MUST** align with the direction of travel on the crossing.
7. At uncontrolled crossings use buff paving, unless otherwise specified on Traffic Signals Drawing.
8. Controlled crossings are Pelican, Toucan, Puffin, Zebra, Pegasus and signalised junctions which incorporate illuminated pedestrian control.
9. Uncontrolled crossings are any crossing not mentioned in Note 8.
10. All requirements to comply with principles set out in DETR 'Guidance on the use of Tactile Paving surfaces' 1998 or subsequent revisions.
11. This dimension is either 0.8m or 1.2m, depending on direction of approach for pedestrians.
12. Tactile paving shall be concrete 'Dimple' blocks (unless otherwise stated) 200mm x 133mm x 60mm laid on 30mm sand, 100mm AC20 dense binder and 150mm type 1 sub-base



**Note:**  
The overall layout of the tactile paving shall result in an 'L' shape.  
An 'J' shape is incorrect and not acceptable.



This is a Standard Detail for Pelican, Puffin, Toucan, Pegasus and Signalised Junctions. Seek advise from the Traffic Signals Engineer for individual sites.

This is a typical detail and may require conversion to a full scheme specific drawing.

NOT TO SCALE  
(all units in millimetres)

**Disclaimer :** Before making use of this detail, any designer or third party must ensure that it satisfies all requirements of the scheme to which it is being applied. Lincolnshire County Council accept no responsibility for third party use of this Standard Detail.


Rev:	Date:	Description:	Approved by:
AMENDMENT DETAILS			



Checked by:	GP	Approved by:	SB
-------------	----	--------------	----

ISSUED 12/05/17

Layout at Controlled Crossings  
(Red Tactile Paving) on Radii

SD/11/25  
Standard Detail Number

Revision Number